

5800

Door/Window Transmitters



The 5800 Series of door and window wireless transmitters provide the most reliable, convenient and cost effective solutions for security protection. Powerful and versatile, these devices have been designed to solve the toughest, most labor-intensive installations—saving time and money.

With a demonstrated outdoor range of over a mile, the 5800 Series are the industry's best performing wireless transmitters.

FEATURES AND SPECIFICATIONS

5800MINI Door/Window Contact

Featuring an LED status indicator and a sleek, compact design, the 5800MINI is ideal for ornate doors, windows, casements and any application where aesthetics are critical.

- Signal transmission and low battery LED indicators
- Single-zone transmitter
- Sleek design virtually disappears
- Transmits supervisory, tamper and low battery
- Case tamper protection
- Magnet included
- Ideal for double-hung windows
- 3V lithium battery included
- Sensor dimensions:
1" W x 2.2" H x 0.25" D
(25.4mm x 55.9mm x 6.4mm)
- Magnet dimensions:
0.25" x 0.25" x 1"
(6.4mm x 6.4mm x 25.4mm)
- ETL Listed
- Operating Wireless Frequency: 345 MHz

5814 Ultra Small Door/Window Transmitter

The 5814 provides the perfect solution for difficult to reach places and applications where aesthetics and small size are important.

- Ideal for ornate doors/windows, casements, etc.
- Extremely compact
- Features a built-in reed switch and tamper
- Includes a supervised, replaceable CR2430 battery
- Dimensions:
1-1/2" H x 1-3/16" W x 5/8" D
(38.1mm x 30.2mm x 15.9mm)

5815 Door/Window Transmitter

The 5815 is the ideal solution for installations where small size and aesthetics are important. It provides a reliable, convenient and cost-effective solution for door and window protection.

- New sleek design
- Two reed switches
- Transmits supervisory, tamper and low battery messages
- Includes a supervised replaceable CR123 battery
- Dimensions:
3" H x 1-1/2" W x 7/8" D
(76.2mm x 38.1mm x 22.2mm)
- UL Listed

5815WG Door/Window Transmitter

When you need extra gap on an installation, select the 5815WG.

- Sleek design
- Wide gap contact over 1.0"
- Single reed switch
- Aux terminals for wired devices
- Includes supervised, replaceable CR123 battery
- Dimensions: 3" H x 1-1/2" W x 7/8" D
(76.2mm x 38.1mm x 22.2mm)
- UL Listed

5816 Door/Window Transmitter

Two zone transmitter with both built-in magnetic reed switches and wired closed circuit contact loop.

- Features a standard white plastic case. Brown cases available in packs of three (5816BR).
- Includes a supervised replaceable CR123 battery
- Four pack of spare magnets (5899)
- Dimensions:
3-1/16" H x 1-9/16" W x 1-3/16" D
(77.8mm x 39.7mm x 30.2mm)
- UL Listed
- Operating Wireless Frequency: 345 MHz

5800

Door/Window Transmitters

FEATURES AND SPECIFICATIONS

5817XT Three Zone Universal Transmitter

Three zone transmitter with three separate contact loops. Primary loop supports normally open and normally closed applications and fast loop response time. The two auxiliary loops support conventional normally closed contact applications.

- Features a normal zone response time of 200msec; the fast zone response is 5msec
- Includes a supervised replaceable CR123 battery
- Dimensions: 3-1/2" H x 1-9/16" W x 1-3/16" D (88.9mm x 39.7mm x 30.2mm)
- UL Listed

5817CBXT Wireless Light Commercial Transmitter

The 5817CBXT is a universal contact-monitoring transmitter that can be used with household and light commercial fire and burglary-initiating devices.

- Approved for use in light commercial fire and burglary
- The 5817CBXT has three unique input loops (zones)

- The first loop (primary loop) is supervised and typically used for high-priority alarm reporting such as light commercial fire or burglary
- The second loop is the built-in, normally closed reed switch used in conjunction with magnet
- The third loop is another normally closed household burglary loop
- A fourth (automatically enrolled) loop contains two tamper switches to protect the 5817CBXT
- Dimensions: 3-1/2" H x 1-9/16" W x 1-3/16" D (88.9mm x 39.7mm x 30.2mm)
- UL Listed

5818MNL Recessed Door/Window Transmitter

The 5818MNL is a magnetic contact sensor that provides concealed protection for doors or windows.

- Includes self-contained transmitter and reed sensor
- Virtually disappears once installed
- Easy replaceable AAA Lithium battery
- 0.5" gap (transmitter to magnet)

- Features a tapered cylinder for easy and flush fit
- Dimensions: 0.75" (19.05mm) diameter x 3.0" (76.2mm) length
- UL Listed

5820L Door/Window Contact Transmitter

The 5820L is nearly half the size of standard door/window transmitters. It is ideal for casement and double-hung windows.

- Sleek design is nearly half the size of competitors
- Case tamper protection (front and back)
- Ideal for double-hung windows
- Easy replaceable AAA Lithium battery
- Dimensions: 3.0" H x 0.5" W x 0.8" D (76.2mm x 12.7mm x 20.3mm)
- UL Listed

ORDERING

5800MINI	Door/Window Contact supplied with Lithium battery (white)	5817CBXT	Wireless Light Commercial Transmitter (UL Light Commercial Approved for Fire and Burglary)
5814	Ultra Small Door/Window Transmitter	5818MNL	Recessed Door Transmitter with Lithium battery supplied
5815/5815WG	Door/Window Transmitter	5820L	Slimline Door/Window Contact Transmitter supplied with Lithium battery
5816	Door/Window Transmitter	5899	Four pack of spare magnets for 5816
5817XT	Three Zone Universal Transmitter		

For more information

resideo.com/pro



For more information
resideo.com

Resideo Technologies, Inc.

2 Corporate Center Drive,
Suite 100
P.O. Box 9040
Melville, NY 11747
1-800-645-7492

L/5800TRAND/D | JC | 06/23
© 2023 Resideo Technologies, Inc.
All rights reserved.